

Beamer Scooter 2004 Specifications

| | | (Model No. PN2) | |
|--------------------------------|-------|-----------------------------------|--|
| Engine | | | |
| Type | | Two cycle air cooled oil injected | |
| Displacement | | 49.3cc | |
| Bore / Stroke | | φ40.0 * 39.2mm | |
| Compression - Ratio / Pressure | | 6.8:1 / 90-120psi | |
| Torque / BHP | | 5.2N m @ 7000rpm / 1.5BHP | |
| Estimated MPG City/Highway | | 85mpg/95mpg | |
| Transmission | | | |
| Туре | | Automatic (C.V.T. V-Belt) | |
| Chassis | | | |
| Overall Length | | 1830mm / 72.0" | |
| Overall Width | | 650mm / 25.6" | |
| Overall High | | 1100mm / 43.3" | |
| Wheel Base | | 1260mm / 49.6" | |
| Dry Weight | | 82kg / 180.7lb | |
| Suspension | | | |
| Front | | Telescopic Fork | |
| Rear | | Unit Swing Arm / Single Shock | |
| Brakes | | | |
| Front | | Hydraulic Disc | |
| Rear | | Mechanical Drum | |
| Tires | | | |
| Front | | 120/90-10 | |
| Rear | | 130/90-10 | |
| Tire Pressure | Front | Front 18psi / 1.25kg/cm2 (Cold) | |
| | Rear | Rear 25psi / 1.75kg/cm2 (Cold) | |

| Beamer Scooter 2004 Specifications | | |
|---|--------|--|
| | | (Model No. PN2) |
| Carburetor | | |
| Make/Size | | Mikuni 18mm (Electrical Coke) |
| Main Jet | | 85mm |
| Pilot Jet | | 20mm |
| Air Mixture Adjustment | | Back out ³ / ₄ - 1 ¹ / ₄ turns |
| Idle Speed | | Idle 1700 - 1900rpm |
| Battery | | |
| Jell Acid (Maintenance Free) | | 12V-4AH/5AH - GTX5L-BS |
| Fluids | | |
| Fuel | Type | Unleaded Gasoline 89 octane |
| | Volume | 5.5liters / 1.5gal |
| 2 Cycle Oil | Type | High grade synthetic 2 cycle injector oil |
| | Volume | 1.1 liters / 1.2qts |
| Transmission | Type | SAE 80/90 weight |
| | Volume | 100cc / 3.4oz |
| Jell Acid | | 4.65 |
| NGK (recommended) | | BPR7HS |
| Nipendenso | | W22FRP-U |
| Champion | | QL82YC |
| Electrode Gap | | 0.6-0.7mm / 0.023" |
| Max Driver & Passenger Weight | | 150kgf / 330lbs. |
| Available Colors *Subject to availability | | Red |
| | | Blue |
| | | Yellow |
| | | Black |