

## 2005-07 VIPER 70 ATV Specifications

			(Model No. RXL-70)
Engine			
Type			Two cycle air cooled
Displacement			68.0cc
Bore / Stroke			φ47.0 * 39.2mm
Compression Ratio / Pressure			8.3 : 1 / 90-100psi
Torque / BHP			6.3N m @ 6000rpm / 6.0BHP
Starting			Electrical with Kick starter back up
Transmission			
Туре			Automatic (C.V.T. V-Belt)
Chassis			
Overall Length			1470mm / 57.9"
Overall Width			850mm / 33.5"
Overall High			830mm / 32.7"
Wheel Base			930mm / 36.1
Seat Height			650mm / 25.5"
Ground Clearance			127mm / 5"
Dry Weight			108kg / 238lbs
Suspension			
Front			Independent Front A-arm with Adjustable Shocks
Rear			Swing Arm Shock with Adjustable Shock
Brakes			
Front			Dual Mechanical drum
Rear			Hydraulic Disc
Tires			
Front			16/8-7
Rear			16/8-7
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2

2005-07 VIPER 70 ATV Specifications				
		(Model No. RXL-70)		
Wheels				
Bolt Pattern		4 x 110mm		
Carburetor				
Make/Size		SW 18mm (Manual Coke)		
Main Jet		85mm		
Pilot Jet		20mm		
Air Mixture Adjust	tment	Back out <sup>3</sup> / <sub>4</sub> - 1 <sup>1</sup> / <sub>4</sub> turns		
Idle Speed		Idle 1700 - 1900rpm		
Sprockets				
Front		520x15t		
Rear		520x28t		
Chain		#520		
Battery				
Jell Acid (Mainter	nance Free)	12V-4AH/5AH - GTX5L		
	Main Fuse	7Amp		
Fluids				
Fuel	Type	Unleaded Gasoline 89 octane		
ruei	Volume	4.5liters / 1.2gal		
	Type	High grade synthetic		
Engine Oil		2 cycle oil		
	Volume	1.0liters / 1gt		
Transmission	Туре	SAE 80/90 weight		
	Volume	100cc / 3.4oz		
Spark Plug		XV		
NGK		BPR7HS		
Nipendenso		W22FRP-U		
Champion		QL82YC		
Electrode Gap		0.6-0.7mm / 0.023"		
Safety Features				
Remote Control St	op/Start	Optional Kit		
Safety Tether Swite	ch	Standard equipment		
Enclosed Foot Res	t Area	Standard equipment		
Enclosed Engine co	ompartment	N/A		
Maximum Rider	Weight	68.2kg / 190lb		
Minimum Rider A		6 years		
		Red		
Availah	le Colors	Blue		
	availability	Yellow		
•		Black / Yellow		