

## Rover GT



Shown with optional equipment

## Let the ROVER GT take you there!

Mountain Silver Forest Green

Introducing the 2007 E-TON Rover GT Utility Kart. E-TON's brand-new, versatile, unique sport/utility vehicle includes a powerful four-stroke air cooled engine, automatic C.V.T. belt transmission with forward/reverse shifting, a full body frame with a seat belt, and a U.S. Forest Service approved spark arrestor.

The Rover GT meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. This multi-purpose vehicle was designed for appropriate sized riders of all ages

## **Optional Accessories**

- Portable Cooler
- Helmets and apparel
- Remote Stop Switch
- Front Cargo Rack
- Rear Cargo basket
- 2 styles of Cargo bags

All available through your local dealership and our website.

**EON** AMERICA.

www.etonamerica.com

	by <b>E-TON</b>
Engine	
Type	Four cycle air cooled (EPA Compliant) SOHC
Displacement	88.4cc
Bore / Stroke	φ47.0 * 51.0mm
Compression Ratio / Pressure	10.2 : 1 / 120-140psi
Torque / Power	6.1N ms @ 4000rpm / 6.4Ps/8000rpm
EPA Approved	Meet or exceeds EPA clean air requirements and CA Green Sticker
Spark Plug	Recommended: NGK CR7HSA/NGK or Nipendenso U22FS-U
Electrode Gap	0.6-0.7mm or 0.023"
Starting	Electrical starter
Transmission	
Type	Automatic (C.V.T. V-Belt) with forward/reverse shift
Chassis	
Overall Length-Width-Height	2110mm / 83.0" - 1000mm / 39.4" - 1110mm / 43.7"
Wheel Base	1375mm / 54.1"
Seat Height	710mm / 28.0"
Dry Weight	185 kg / 407.9 lbs
Suspension	105 kg / 407.5 lbs
Front	A-arm with dual Adjustable Shocks
Rear	Swing Arm with Adjustable Shock
Brakes	
Front	155mm Dual Hydraulic Disc
Rear	175mm Hydraulic Disc
Tires	
Front	18/7-10
Rear	18/8-10
, Min	3.2psi / 0.23kg/cm2
Front Max	4.0psi / 0.28kg/cm2
Tire Pressure Min	3.2psi / 0.23kg/cm2
Rear Max	4.0psi / 0.28kg/cm2
Wheels	
Bolt Pattern Front	4 x 110mm (P.C.D.)
Rear	4 x 110mm (P.C.D.)
Carburetor	
Make/Size	SVR 22mm with Manual Choke
Main Jet	0.95mm
Pilot Jet	0.32mm
Air Mixture Adjustment	Back out 1½ - 1¾ turns
Idle Speed	Idle 1700 - 1900rpm
Sprockets	
Front	520x12t
Rear	520x32t
Chain	#520
Battery	
Jell Acid (Maintenance Free)	12V-5AH - GTX5L
Fluids	
Fuel Type	Unleaded Gasoline 92 octane
Volume	11 liters / 2.9gal
Engine Oil Type	SAE 15W-40
Volume	0.9liters / 0.23gal
Transmission Type Volume	SAE 80W-90 300cc / 10.20z
Safety Features	JULE / 10.20L
Seat Belt	Lap Belt (Standard)
Remote Stop Switch	Remote Engine Stop Switch (Optional)
Carrying Capacity	
Maximum Rider Weight	100kg / 200 lbs
Additional Features	
Rear Cargo Flat Bed (Standard)	Digital dash gauge—Speedometer & Fuel Level (Standard)
Covered Front Storage Compartment	Dash mounted F/R Shift Knob & indicator lights (Standard)
(Standard)	Trailer Hitch & Accessory Power Outlet (Optional)
Sporty Steering Wheel	Foot peddle throttle & brakes controls (Standard)
Rear Cargo Basket (Optional)	Front Cargo Rack (Optional)
Detachable Spot Light (Optional)	Carpeted floor mat (Optional)
2 continuor opot Eight (Optional)	Carpered neet inut (Optional)