

Matrix R4

by **E-TON**



Just go there!

Matrix R4

Metallic Red Deep Sea Blue

Introducing the E-TON Matrix 150 Scooter, the next generation of the popular Beamer Matrix scooter line. This Beamer is powered by a 150cc 4 cycle engine that gives you great performance and an economical transilveration alternative. With estimated mileage of 120 MPG*, the Matrix 150 is easy on the fuel bill.

This model is EPA approved and meets or exceed all other Federal DOT regulations.

The Matrix 150 is fully decked out with our Powder Coat 12" Aluminum Mag-Wheels and front and rear Hydraulic Disc HydrDisc® Brakes, and dual shock rear suspension.

The Silvery look of the Matrix 150 gives you a stylish economical ride.

Engine		
Type		Four cycle air/oil cooled (EPA Compliant) SOHC
Displacement		149.5cc
Bore / Stroke		φ57.4 * 57.8mm
Compression Ratio / Pressure		9.7 : 1 / 150-190psi
Torque Max Speed		10.5N m @ 6000rpm 110kph - 70mph
		Tokhi /ompi
EPA Approved		Meet or exceeds EPA clean air requirements and CA Green Sticker
Estimated MPG		120+ MPG (MPG under test conditions)
Starting Transmission		Electrical starter with kick start backup
Transmission Type		Automatic (C.V.T. V-Belt)
Chassis		Automatic (C.V.I. V-Belt)
Overall Length		1915mm / 75.2"
Overall Width		655mm / 25.8"
Overall Height		1015mm / 40.0" (1270mm/50.2" w/ mirrors)
Seat Height		780mm/30.1"
Wheel Base		1355mm / 53.3"
Dry Weight		112.5kg / 248.0 lb
Suspension		114305 / 2100 10
Front		Telescopic Fork, Travel 75mm/3.0"
Rear		Dual Adjustable Shocks, Travel 45mm/1.8"
Brakes		
Front		180mm HydrDisc [©] Hydraulic Disc
Rear Tires		180mm HydrDisc [©] Hydraulic Disc
		2007040
Front		120/70-12 — 18psi / 1.25kg/cm ² (Cold)
Rear		130/70-12 — 25psi / 1.75kg/cm ² (Cold)
Carburetor		
Make/Size		Kei-Hin CVEK-019 26mm with Manual Choke
Main Jet		1.12mm
Pilot Jet		0.35mm
Air Mixture Adjustment		Back out 1 - 2½turns
Idle Speed		Idle 1600 - 1800rpm
Battery		
Lead Acid (Maintenance Free)		12V-8AH
	Main Fuse	10Amp
Fluids		
riulus	Туре	Unleaded Gasoline 89 octane
Fuel	Volume	6.5 liters / 1.7gal
Engine Oil	Туре	SAE 20w-40
	Volume	
Transmission		1.0 liters / 1.0 qt
	Type	SAE 80W/90
Spark Dlug	Volume	300cc / 10.2 oz
Spark Plug NCK (recommended)		
NGK (recommended)		BPR7HS
Nipendenso		W22FRP-U
Champion		QL82YC
Electrode Gap		0.6-0.7mm / 0.023"
GVWR (Total)		240kg. / 530lbs.
(Front)		76kg. / 167lbs.
(Rear)		165kg. / 164lbs.
Two Dossongon / Weight Limit		branch () () () () ()

Two Passenger / Weight Limit YES / 112kg. / 300lbs.

ETON America

www.etonamerica.com