

Viper 70



Just go there!

Viper 70

Cherry Red Royal Blue Sunlight Yellow Black & Yellow

Introducing the 2007 E-TON Viper 70 four-stroke ATV. This Viper includes a 69.3cc four-stroke aircooled engine, Automatic C.V.T. belt transmission, and a U.S. Forest Service-approved spark arrestor. The 2007 Viper 70 meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. Designed for riders ages 6 and up.

Optional Accessories

- Remote stop switch
- Safety tether switch
- Hi-Flo fuel line kit
- 3" clear stone fuel filter
- Colored handlebar grips
- Tire repair kit
- E-TON safety flag
- Helmets and apparel available on the web site

EON AMERICA.

www.etonamerica.com

	by E-TON
Engine	
Type	Four cycle air cooled (EPA Compliant) SOHC
Displacement	69.3cc
Bore / Stroke	φ47.0 * 40mm
Compression Ratio / Pressure	9.0 : 1 /. 110—130psi
Torque / BHP	4.8N ms @ 6500rpm / 6BHP
EPA Approved	Meet or exceeds EPA clean air requirements and CA Green Sticker
Starting	Electrical starter with kick start backup
Transmission	
Туре	Automatic (C.V.T. V-Belt)
Chassis	
Overall Length-With-Height	1480mm / 58.3" - 850mm / 33.5" - 860mm / 33.9"
Wheel Base	930mm / 36.1"
Seat Height	670mm / 26.4"
Ground Clearance	100mm / 3.94"
Dry Weight	112kg / 247lbs
Suspension	
Front	Independent A-arms with Adjustable Shocks
Rear	Swing Arm with Adjustable Shock
Brakes	
Front	Dual mechanical drum
Rear	Hydraulic Disc
Tires	Tryuraunc Disc
Front	16/8-7
Rear	16/8-7
Keai Min	3.2psi / 0.23kg/cm2
Front Max	4.0psi / 0.28kg/cm2
Tire Pressure Min	3.2psi / 0.23kg/cm2
Rear Max	4.0psi / 0.28kg/cm2
	4.0psi / 0.2okg/cm2
Wheels	4 110 (BCB)
Bolt Pattern Front	4 x 110mm (P.C.D.)
Rear	4 x 110mm (P.C.D.)
Carburetor	CWI 40
Make/Size	SW 18mm (Manual Choke)
Main Jet	0.95mm
Pilot Jet	0.32mm
Air Mixture Adjustment	Back out 1½ - 1¾ turns
Idle Speed	Idle 1700 - 1900rpm
Sprockets	
Front	520x13t
Rear	520x28t
Chain	#520
Battery	
Jell Acid (Maintenance Free)	12V-4AH/5AH - GTX5L
Main Fuse	7Amp
Fluids	
Fuel Type	Unleaded Gasoline 89 octane
Volume	4.5 liters / 1.2 gal
Engine Oil Type	SAE 20W - 40
Volume	0.8 liters / 0.84 qt
Type Type	SAE 80W/90
Transmission Volume	120cc / 4.1 oz
Safety Features	
Safety Tether Switch	Optional equipment
Remote Stop Switch	Optional equipment
Enclosed Foot Rest Area	Standard equipment
Enclosed Engine compartment	Standard equipment
Carrying Capacity	
Front	N/A
Rack Capacity Rear	N/A
Towing Capacity Trailer Wgh	N/A
	N/A
Tongue Wgh	N/A
Maximum Rider Weight Minimum Rider Age	68.2kg / 190lb
VIIIImiim Rider Age	6 years