



Rover

by **E-TON**



Shown with optional equipment

Just go there!

Rover

Flame Red
Royal Blue

Introducing the 2007 E-TON Rover Utility Kart. E-TON's brand-new, versatile, unique sport/utility vehicle includes a powerful four-stroke air cooled engine, automatic C.V.T. belt transmission with forward/reverse shifting, a full body frame with safety nets and a seat belt, and a U.S. Forest Service approved spark arrestor.

The Rover meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. This multi-purpose vehicle was designed for appropriate sized riders of all ages

Optional Accessories

- Navigational Compass
- Portable Cooler
- Helmets and apparel
- Remote Stop Switch
- Wind Shield

Available through your local dealership and our web-

EON AMERICA.

www.etonamerica.com

Engine			
Type	Four cycle air cooled (EPA Compliant) SOHC		
Displacement	88.4cc		
Bore / Stroke	φ47.0 * 51.0mm		
Compression Ratio / Pressure	10.2 : 1 / 120-140psi		
Torque / BHP	6.5N ms @ 6500rpm / 4.8BHP		
EPA Approved	Meet or exceeds EPA clean air requirements and CA Green Sticker		
Spark Plug	Recommended: NGK CR7HSA/NGK or Nipendenso U22FS-U		
Electrode Gap	0.6-0.7mm or 0.023"		
Starting	Electrical starter		
Transmission			
Type	Automatic (C.V.T. V-Belt) with forward/reverse shift		
Chassis			
Overall Length-Width-Height	1766mm / 69.9" - 1020mm / 40.2" - 1675mm / 65.9"		
Wheel Base	1108mm / 43.6"		
Seat Height	700mm / 26.6"		
Dry Weight	162 kg / 356 lbs		
Suspension			
Front	Swing A-arm with dual Adjustable Shocks		
Rear	Swing Arm with Adjustable Shock		
Brakes			
Front	Dual Hydraulic Disc		
Rear	Hydraulic Disc		
Tires			
Front	18/7-10		
Rear	18/8-10		
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
Wheels			
Bolt Pattern	Front	4 x 110mm (P.C.D.)	
	Rear	4 x 110mm (P.C.D.)	
Carburetor			
Make/Size	SVR 22mm with Manual Choke		
Main Jet	0.95mm		
Pilot Jet	0.32mm		
Air Mixture Adjustment	Back out 1½ - 1¾ turns		
Idle Speed	Idle 1700 - 1900rpm		
Sprockets			
Front	520x12t		
Rear	520x32t		
Chain	#520		
Battery			
Jell Acid (Maintenance Free)	12V-4AH/AH - GTX5L		
Fluids			
Fuel	Type	Unleaded Gasoline 92 octane	
	Volume	11liters / 2.9gal	
Engine Oil	Type	SAE 15W-40	
	Volume	0.9liters / 0.23gal	
Transmission	Type	SAE 80W-90	
	Volume	300cc / 10.2oz	
Safety Features			
Speed Control	Ignition Key Speed Control (Standard)		
Remote Stop Switch	Remote Engine Stop Switch (Optional)		
Safety Catch Netting	Rider compartment Safety Netting (Standard)		
Seat Belt	Lap Belt (Standard)		
Carrying Capacity			
Maximum Rider Weight	86.2kg / 190 lbs		
Additional Features			
Rear Cargo Bed	Accessory Power Outlet		
Covered Front Storage Compartment	Foot peddle throttle and brakes controls		
Sporty Split Steering Wheel	Dash mounted Forward / Reverse Shift Knob		
Adjustable Head Rest	Optional Floor mat and bed liners		



